



Power Quality acc. to
IEC 61000-4-30 ed.3

- ✓ Modern Control
- ✓ Touchscreen
- ✓ Large Data Storage
- ✓ Battery
- ✓ GPS
- ✓ Harmonic Analysis up to 9 kHz
- ✓ Power and Energy
- ✓ Disturbances
- ✓ Waveform Capture
- ✓ Symmetrical Components

ENA7000

Class A Portable Power
Quality Analyzer

ENA7000

The firmware calculates power quality parameters according EN50160 fully follows requirements described in IEC 61000-4-30 Class A and others (61000-4-7, 61000-4-15).

MAIN MEASUREMENT FUNCTIONS ARE:

- › U, I, P, Q, S, frequency, THD U, THD I, power factor, energies – AP, AQ, AS, APin, APout, all quantities are per phase and total
- › Harmonics – U, I, P, Q up to 50th harmonic, U and I also as 200Hz spectra (0-9 kHz)
- › Symmetrical components - three-phase system decomposition into a positive, negative, and zero component
- › All quantities are calculated on 200 ms (10/12 period basis) according to IEC 61000-4-30
- › Voltage quality according to EN50160, IEC 61000-4-30 Class A (U, freq., THD U, flicker, unbalance, harmonics)
- › Voltage events according EN50160, IEC 61000-4-30 Class A (dip, swell, interruption – time, extrema, length)
- › Waveform capture (transients) – in case of trigger, the device captures the waveform
- › Trigger can be activated by selected quantities (U, I, P, Q, S, freq., PF) crosses specified limits
- › Waveform means raw voltage/current signal with sampling rate at 9,6 k/19,2 k per second, waveform length is up to 60 periods, with pre-trigger up to 1.2 second
- › Disturbances – in case of trigger, the device captures the half-period RMS quantities
- › Trigger can be activated by selected quantities (U, I, P, Q, S, freq., PF) crosses specified limits
- › Capture contains half-period quantities of voltage, current, frequency, power etc. (sampling rate is 100 samples per second), capture length is up to 15 minutes, with pre-trigger up to 30 seconds

FUNCTIONALITY

VOLTAGE INPUT

Channels	4
Input Range	500 V (Measuring up to 1000 V)
Accuracy	0.05 %
Isolation Voltage	6 kV
Impedance	10 MOhm

CURRENT INPUT

Channels	4
Current Clamps	Clamps, Rogowski Coils
Input Range	Acc. to the sensors, typical 5 A for clamps, 3000 A for Rogowski Coils
Accuracy	Clamps 0.1 %, Rogowski Coils 0.5 %

HARDWARE

Display	7", touchscreen
Data Storage	256 GB
Interfaces	USB, Ethernet, Wi-Fi
A/D Conversion	Sigma-delta
Sampling Rate	48 kSa/s,
Power Supply	100 VAC - 240 VAC
Battery	2 hours
Class	CATIV 600 V

OTHERS

Optional Interfaces	GPS
---------------------	-----

PARAMETERS